

Electrochemistry Meter AL15

**dissolved Oxygen (O₂) | O₂-concentration in mg/l
Conductivity/TDS | pH/Redox | °C/°F - All in One**



90

Applications

- Drinking Water
- Cooling/Boiler Water
- Waste Water
- Pool Water
- Surface Water
- Water Treatment Companies
- Industrial and Governmental Laboratories

The AL15 combines the features of several electrochemistry meters. It is designed for multi purpose operation and measures pH/Redox, dissolved oxygen and conductivity/TDS.

The AL15 incorporates an intuitive user interface, large, easy to read display and is supplied with a sturdy handy case with electrodes, buffer solution and accessories.

AL15

Display	Large LCD display with contrast adjustment
Measurement	pH: 0 to 14.00 pH ORP: ± 1999 mV Conductivity: 200 μ S / 2 mS / 20 mS / 200 mS TDS (Total Dissolved Solids): Dissolved Oxygen: 0 to 20.0 mg/l
Data Logger	Real time data logger
Data Memory	Auto or manual data memory, 16000 data sets
Data Hold	Max, Min
Interface	USB, RS232
Probes	pH, ORP, Conductivity/TDS, Dissolved Oxygen and ATC
Power off	Auto shut off or manual off
Data Output	RS 232 PC serial interface
Power Supply	DC 1,5 V battery (UM3, AA) x 4 PCs or DC 9V adapter in
Software	Data acquisition software Data logger software
Approval	CE

pH/Redox

Range	pH 0 to 14 PH mV -1999 mV to 1999 mV
Resolution	0 - 14 pH, 0.01 pH 0 - 1999 mV, 1 mV
Accuracy	0 - 14 pH, ± 0.02 pH + 2 digits 0 - 1999 mV, ± 0.5 % + 2 digits
Temperature Compensation	manual 0 - 100 °C automatic (ATC)
pH Calibration	pH 7, pH 4, and pH10, 3 points calibration

Oxygen

Range	Dissolved Oxygen 0 to 20.0 mg/l (liter) Oxygen in Air 0 to 100.0 % Temperature 0 to 50 °C
Resolution	Dissolved Oxygen 0.1 mg/l 0.1 % O ₂ Temperature 0.1 °C
Accuracy (23 \pm 5 °C)	Dissolved Oxygen ± 0.4 mg/l Oxygen in Air ± 0.7 % O ₂ Temperature ± 0.8 °C / 1.5 °F
Salinity Correction	0 to 39 % Salt
Air Pressure Comp.	0 to 8900 meter

Conductivity/TDS

Range/ Resolution	Conductivity (μ S, mS) 0 - 200.0 μ S / 0.1 μ S 0.2 - 2.000 mS / 0.001 mS 2 - 20.00 mS / 0.01 mS 20 - 200.00 mS / 0.1 mS TDS (Total Dissolved Solids) 0 - 132 ppm / 0.1 ppm 132 - 1,320 ppm / 1 ppm 1,320 - 13,200 ppm / 10 ppm 13,200 - 132,000 ppm / 100 ppm Temperature 0 - 60 °C / 0.1 °C ; 32 - 140 °F / 0.1 °F
Accuracy	± 2 % F.S. + 1 digit ; ± 0.8 °C / ± 1.5 °F
Function	Conductivity (μ S, mS) TDS (Total Dissolved Solids, PPM) Temperature (°C, °F)

Delivery Content

Code	Article
4724200	AL15 Set pH / Con / Oxi instrument, batteries, pH electrode, temperature probe, conductivity probe, oxygen sensor, pH buffer set 4,00 / 7,00, electrolyte, membrane heads, instruction manual, warranty information, in case
4724210	AL15 Set pH / Con instrument, batteries, pH electrode, temperature probe, conductivity probe, pH buffer set 4,00 / 7,00, instruction manual, warranty information, in case
4724220	AL15 Set pH / Oxi instrument, batteries, pH electrode, temperature probe, oxygen sensor, pH buffer set 4,00 / 7,00, electrolyte, membrane heads, instruction manual, warranty information, in case
4724230	AL15 Set pH / Redox instrument, batteries, pH electrode, temperature probe, redox electrode, pH buffer set 4,00 / 7,00, instruction manual, warranty information, in case

Accessories

Code	Article
721330	Spare electrode plastic/gel type BNC-plug
721250	pH buffer set 4.01/7.00/10.01 (25°C)
721247	pH buffer, 4.01 (25°C), 90 ml
721248	pH buffer, 7.00 (25°C), 90 ml
721249	pH buffer, 10.01 (25°C), 90 ml
721252	pH buffer 4.01 (25°C) 1 litre
721254	pH buffer 7.00 (25°C) 1 litre
721256	pH buffer 10.01 (25°C) 1 litre
721242	Redox electrode plastic/gel type BNC-plug
195070	Redox calibration solution, 470 mV, 100 ml
724400	Conductivity probe
722250	Calibration solution 1413 μ S/cm
724410	Oxygen sensor
724460	Spare membrane for oxygen sensor
724470	Spare electrolyte for oxygen sensor
724420	Temperature probe PT1000
724500	RS232 cable, for connection to a computer
724510	USB cable, for connection to a computer
724540	Power supply
725050	Case incl. foam
4724520	Data Retrieve Software Software which enables the user to transmit data stored on the instrument to a computer
4724530	Data Logger / Aquisition Software Software which enables the user to monitor and log data on a computer (online measurement)

Highlights

- pH/Redox
Conductivity
Dissolved Oxygen etc.
- All in one
- Real time data logger
- Large digital display
- Protective casing
- RS 232 / USB