

Photometer AL400 & AL410

Modern, mobile photometers
for rapid, reliable water testing



The AL410 and AL400 give you mobile devices in a modern design with the analytical features of laboratory photometers.

All important water analysis parameters from A(luminium) to Z(inc) are covered by these two devices. Combined with the high precision of AQUALYTIC® reagents, a reliable and quick analysis of water samples is guaranteed. Reagent tablets, powder reagents, liquid reagents, or cuvette tests are used depending on the method.

Six long-lasting LEDs serving as a light source in combination with interference filters guarantee the highest precision. The devices

are designed without moving optical parts and thus have a maintenance-free measuring unit. Up to 1,000 data records can be stored in both the AL410 and the AL400.

The **AquaLX®** app, available free of charge, offers the possibility of transferring measurements to smart phones or tablets via **Bluetooth®**. The data management then enables analysis and export as a CSV file or graph via email. The app is available free of charge for Android™ and iOS®.

The proven AL400 photometer uses the classic infrared interface with which data can be transferred by means of the IRIM module to the PC or laptop.

22

Highlights

- Highest/reproducible precision with interference filter
- Display with background lighting
- More than 120 pre-programmed methods
- Automatic selection of wavelength
- User guidance in German, English, French, Spanish, Italian, Portuguese (BR), Polish, and Indonesian.
- Buffer for up to 1000 data records
- More than 35 user-specific methods possible
- Bluetooth® interface for connection to smart phones and tablets (only with AL410)
- iOS® and Android™ app for data management and email delivery (only with AL410)
- Infrared interface (only with AL400)
- Waterproof housing*
- Handheld format, portable

* as defined in IP 68, 1 hour at 0.1 meter

The Bluetooth® word mark is a registered trademark owned by Bluetooth SIG, Inc. and any use by AQUALYTIC® Tintometer GmbH is under license. iOS® is a registered trademark of Cisco, Inc. and licensed to Apple, Inc. Android™ is a trademark of Google, Inc.

N.I.S.T. Traceability

The instrument has a factory calibration, which is related to international standards, which are not N.I.S.T traceable. The instrument may be calibrated by the user in a "user calibration mode" with N.I.S.T traceable standards.

(N.I.S.T. = National Institute of Standards and Technology)

New methods

Test methods are regularly updated to suit market requirements. You can find software updates for new methods and additional languages on our website at www.aqualytic.de.

Polynomials

With the help of an external mathematical program, the corresponding polynomial is created from data pairs (concentration/absorption). A known polynomial may also be used. 25 order polynomials ($y = A+Bx+Cx^2 + Dx^3 + EX^4 + FX^5$) can be stored together with user-specific parameters such as wavelength, measuring range, unit and number of decimals.

Concentration

This function can be used to measure 2 to 14 known standards. On the basis of the concentrations/absorption pairs obtained, the photometer will calculate a linear interpolation between the measured points. Up to 10 methods can be stored for further sample measurements.

Delivery Content

The instrument is supplied complete and ready-to-use incl. 4 batteries, 3 cuvettes ø 24 mm, 3 cuvettes ø 16 mm, 1 adapter each for 16 mm and 13 mm cuvettes, stirring rod 13 cm, brush 11 cm, screw driver, warranty information, certificate of compliance, instruction manual, carrying case with water resistance foam, **but without reagents.**


Order codes

AL400: 4214020

AL410: 4214025

Please specify the reagents or parameters required at time of order.

You can find updated information on parameters and measuring ranges on our website at www.aqualytic.de

 **Reagents (order codes),**
please see pages 40 onwards



Applications

- Waste Water
- Drinking Water
- Industrial Process Water
- Scientific & Research
- Governmental and Private Laboratories
- Mobile Application

Bluetooth® is a wireless technology subject to regional approval. The use of the AL410 with Bluetooth® is currently only permitted within the EU, the USA, and in Canada. The use of the AL410 will also be possible in other regions in the future. For current regions and further information, visit: www.aqualytic.de/bluetooth

Regions in which the AL410 with Bluetooth® can currently be used (status: 01/2015):

within the EU (according R&TTE Directive 1999/5/EC) ; USA (according to FCC part 15, comprised in FCC ID QOQBT113) ; Canada (comprised in IC 5123A-BGTBLE113)

Photometer AL400 & AL410




Technical Data

Display	Graphic-display
Interfaces	Infrared ¹ (AL400), Bluetooth® 4.0 (AL410) RJ45 socket for Internet updates ²
Optics	LEDs, interference filters (IF) and photo sensor in transparent sample chamber Wavelength range: 1 = 530 nm IF $\Delta\lambda = 5$ nm 2 = 560 nm IF $\Delta\lambda = 5$ nm 3 = 610 nm IF $\Delta\lambda = 6$ nm 4 = 430 nm IF $\Delta\lambda = 5$ nm 5 = 580 nm IF $\Delta\lambda = 5$ nm 6 = 660 nm IF $\Delta\lambda = 5$ nm IF = interference filter
Wavelength Accuracy	± 1 nm
Photometric Accuracy*	2% FS (T = 20°C – 25°C)
Photometric Resolution	0,005 A
Operation	Acid and solvent resistant, touch-sensitive keypad with audible feedback via integrated beeper
Power Supply	4 batteries (Mignon AA/LR6); Operation time: approx. 26 h continuous operation or 3500 tests
Auto-Off	approx. 20 minutes after last keypress with audible signal
Dimensions	approx. 210 x 95 x 45 mm (unit) approx. 395 x 295 x 106 mm (case)
Weight (unit)	approx. 450 g
Ambient Conditions	5–40°C at max. 30–90% rel. humidity (non condensing)
Language Selection	German, English, French, Spanish, Italian, Portuguese, Polish, Indonesian; additional languages via Internet update
Memory Capacity	approx. 1000 data sets
Approval	CE

¹ optional available: IRIM (Infrarot Interface Modul)

² optional available: connection cable with integrated electronics
(RS 232 / RJ-45-Buchse)

* tested with standard solutions

 **Reagents (order codes),
please see pages 40 onwards**

Accessories

Item	Code
Set of 12 round cuvettes with lid Height 48 mm, Ø 24 mm	197620
Set of 10 round cuvettes with lid Height 90 mm, Ø 16 mm	197665
Adapter for round cuvettes Ø 16 mm	19802190
Adapter for round cuvettes Ø 13 mm	19802192
Set of multy cuvettes-3 with lids path length 10 mm, 10 ml volume Height 48 mm, Ø 24 mm (12 pc.)	197605
Cuvette stand for 6 round cuvettes Ø 24 mm, acrylic glass	418951
Cuvette stand for 10 cuvettes (Ø 16 mm or □ 13,5 mm), acrylic glass	418957
Sealing ring for cuvette Ø 24 mm (12 pc.)	197626
Battery, 1.5 V, AA-Alkali-Mangan (4 pc.)	1950025
Cleaning cloth for cuvettes	197635
Plastic funnel with handle	471007
Plastic stirring rod, 13 cm length	364100
Plastic stirring rod, 13 cm length, (10 pc.)	364120
Plastic stirring rod, 10 cm length	364109
Plastic stirring rod, 10 cm length, (10 pc.)	364130
Cleaning brush, 10 cm	380230
Verification Standard Kit	4215640
Cable for update for connection to a PC	4214030
Infra-red data transmission modul IRIM	4214050

Verification Standard Kit

The Verification standard kit for the AL400 is designed to reassure the user about the accuracy and the reliability of the results.

The shelf life of the Verification standard kit is two years from the date of production, provided that storage and use are in accordance with the instructions provided. Measurements are taken in mAbs.

Verification Standard Kit

4215640

